OASE GmbH

Tecklenburger Straße 161 D - 48477 Hörstel Phone: +49(0)54 54 - 800 Fax: $+49(0)\dot{5}4^{'}54 - 80322$ info@oase-livingwater.com www.oase-livingwater.com

Aquarius Universal Premium 12000 56879




	Fresh water		Sea water	220- 240 V	400 V	110- 120 V	60 Hz		24 V DC			Plug & Spray
Aquarius Universal Premium		0	0		0	0	0	0	0	0	0	0




Product characteristics at a glance


- Extremely quiet operation
- Easy adjustment of the flow rate
- Integrated thermal protection from 600 onwards
- Suitable for wet or dry installations
- Energy-efficient thanks to low energy consumption
- Frost protected up to -20°C
- High-quality workmanship with stainless steel
- Priming even at low water levels
- Removable pedestal for installation where space is at a premium







Aquarius Universal Premium 5000 - 12000



Aquarius Universal F	Premium 120	000
Dimensions (L x W x H)	[mm]	337 x 161 x 158
Rated voltage	[V/Hz]	220 – 240 V / 50 Hz
Power consumption	[W]	270
Power cable length	[m]	10
Net weight	[kg]	5.45
Max. flow rate	[l/min]	200
Max. flow rate	[l/h]	12000
Max. head height	[m]	7.00
Connection, pressure-side	[inch]	1 ½
Connection, suction-side	[inch]	1 ½
Connection for hoses	[inch]	1, 1 1/4, 1 1/2
Filter intake surface	[cm ²]	223
Electronic adjustment		Yes
Order no.		56879

The information contained in this data sheet is the sole property of OASE GmbH. Any reproduction in part or as a whole without the written permission of OASE GmbH is prohibited. 02.08.2017 AP Version 1.0 sheet 1/1