



The V series is the tank for the classic setups; such as pump and booster settings, potable water, irrigation and sprinkler assembling. The proper using of the tank save the power of the pump. The replaceable membrane fixed between the upper side and the flange avoids scratches and assures the maximum long lasting life.


La gamme V est conçue pour les installations de pompage et surpression. Ces vases réduisent le nombre de démarrages de la pompe et allongent sa durée de vie. Vases à vessie interchangeable à usage alimentaire. La vessie de qualité alimentaire isole l'eau de toute partie métallique.

	Article - Code	Reference Référence	Capacity - Capacité (litre)	Dimensions			Water connection Raccord (male)
				H	E	A	
SANS RACCORD SUPERIEUR	11000024F9	VVEF25 SP*	25	345		362	1"
	11000024F7	VVEF25	25	411		270	1"
	1100003501	VVEF35	35	420		380	1"
	1100005049	VVEF50	50	788	180	380	1"
	1100006068	VVEF60	60	878	170	380	1"
	1100008038	VVEF80	80	848	153	450	1"
	1100010069	VVEF100	100	928	153	450	1"
	11000100AB	VVEF100R	100	950	153	450	1"
AVEC RACCORD SUPERIEUR	1100020069	VVEF200	200	1285	210	550	1 1/2"
	1100030065	VVEF300	300	1415	188	630	1 1/2"
	1100050062	VVEF500	500	1610	188	750	1 1/2"
	1100075069*	VVEF750	750	2125	150	750	1 1/2"
	1100075075	VVEF750	750	2125	150	750	1 1/2"
	1100075071 extra EU	VVEF750	750	2125	150	750	1 1/2"
	1100100074**	VVEF1000	1000	2150	120	850	1 1/2"
	1100100069*	VVEF1000	1000	2150	120	850	1 1/2"
1100100071 extra EU	VVEF1000	1000	2150	120	850	1 1/2"	

Capacities above 1000 litres on request. - Capacités supérieures 1000 litres sur demande.

Reference Référence	Nominal Volume Nominale Volume	Gross weight Poids Brut (Kg)	Poids Net Net weight (Kg)	Volume (M3)	Pieces per pallet Pièces pour palette	Dimensions Dimension
VVEF 25	25	4,3	3,8	0,037	64	100x120
VVEF 25	25	4,6	4,0	0,047	64	120x120
VVEF 35	35	6,7	5,7	0,070	45	120x120
VVEF 50	50	11,3	9,9	0,135	18	80x120
VVEF 60	60	12,0	10,6	0,150	15	90x130
VVEF 80	80	14,4	12,8	0,200	15	100x130
VVEF 100	100	18,6	16,7	0,240	15	100x150
VVEF 100	100	18,6	16,7	0,240	15	100x150
VVEF 200	200	39,6	36,5	0,460	8	110x130
VVEF 300	300	56,6	52,7	0,600	6	125x150
VVEF 500	500	85,2	79,7	1,000	2	80x160
VVEF 750	750	159,0	150,0	1,500	1	80x217
VVEF 1000	1000	218,0	208,7	2,000	1	86x220

Max. working pressure Pression maxi	10 bar *8 bar / ** 6 bar
Working temperature T° min/T° Max	-10° / +99°C
Color of tanks Couleur	ROUGE - RED





V



Accessories - Accessoires

- Easy and fast connection to the pump and to the pressure tank
- Integrated pressure gauge
- Robust plastic fitting with reinforced steel ring replacing common brass fitting
- Optionals
- Customized settings
- Cover with on/off button
- Reinforced electric contacts up to 25A current
- Version with electric cables for line and motor connection



PRS-3W



PRS-2W


- Connection facile et rapide à la pompe et au vase d'expansion.
- Manomètre intégré
- On utilise un raccord solide en plastic équipé avec un anneau en acier renforcé à la place du raccord standard en laiton.
- Accessoires
- Paramètres personnalisés
- Equipé avec un bouton de marche/arrêt
- Contacts électriques renforcés jusqu'à 25A courant
- Modèle équipé avec câbles électriques pour connections en ligne et motorisé

	Article Code	Reference Référence	Capacity Capacité (litre)	Dimensions			Water connection Raccord (male)
				H	L	A	
SANS RACCORD MANO	11000024F8	VHEF25	25	290	411	270	1"
	1100005050	VHEF50	50	410	606	380	1"
	1100006070	VHEF60	60	410	686	380	1"
	1100008039	VHEF80	80	480	686	450	1"
	1100010070	VHEF100	100	480	776	450	1"
AVEC RACCORD MANO	1100010092	VHEF100R	100	480	798	450	1"
	1100020070	VHEF200	200	580	1061	550	1" 1/2"
	1100030066	VHEF300	300	660	1216	630	1" 1/2"


Reference Référence	Nominal Volume Nominale Volume	Gross weight Poids Brut (Kg)	Poids Net Net weight (Kg)	Volume (M3)	Pieces per pallet Pièces pour palette	Dimensions Dimension
VHEF 25	25	5,4	4,9	0,037	56	100x120
VHEF 50	50	11,0	9,9	0,135	25	100x120
VHEF 60	60	11,5	10,2	0,150	15	80x120
VHEF 80	80	13,1	11,6	0,200	15	100x120
VHEF 100	100	17,6	15,8	0,240	15	120x120
VHEF 100	100	17,6	15,8	0,240	15	120x120
VHEF 200	200	39,0	36,5	0,460	8	100x120
VHEF 300	300	55,5	51,0	0,600	6	100x120

Max. working pressure Pression maxi	10 bar
Working temperature T° min/T° Max	-10°/ +99°C
Color of tanks Couleur	ROUGE RED


100R+300 (L) VHEF



25 (L) VHEF



50+100 (L) VHEF



VVEF+BK



Reference Référence	Nominal Volume Nominale Volume	Gross weight Poids Brut (Kg)	Poids Net Net weight (Kg)	Volume (M3)	Pieces per pallet Pièces pour palette	Dimensions Dimension
VVEF+BK 12	12	3,9	3,4	0,031	75	100x120
VVEF+BK 19	19	4,5	4,0	0,037	64	100x120
VVEF+BK 24	24	5,1	4,4	0,043	56	100x120

Article Code	Reference	Capacity Capacité (litre)	Water connection Raccord (male)	Precharge pressure Pression de pré-gonflage	Max. working pressure Pression maxi
11H0001206	VVEF12+BK	12	3/4"G	2,5	10
11H0001908	VVEF19+BK	19	3/4"G	2,5	10
11H0002405	VVEF24+BK	24	3/4"G	2,5	10